CHURTON PACIFIC LIMITED

NATURAL TIMBER FINISHING & PRESERVATIVES
CEDAR RESTORATION SERVICES

TELEPHONE: 64 9 478 4370 FAX: 64 9 478 4370 EMAIL: CHURTON@CHURTON.COM
ADDRESS: 15A VEGA PLACE, MAIRANGI BAY INDUSTRIAL PARK, AUCKLAND
P.O. BOX 302 276, NORTH HARBOUR, AUCKLAND
WWW.CHURTON.COM

Technical Data Sheet

AQUABEAD

Water Repellant & Timber Stabiliser

Characteristics: Aquabead is an environmentally safe, Ultra Violet stable, water repellent which gives excellent long term water exclusion from wood and many other substrates.

Aquabead -

- Provides long term Water Beading
- Does not change the appearance of the substrate - is colourless
- Gives improved dimensional stability on timber (reduces warping & cupping)
- Is stable in high Ultra Violet situations
- Other products can be applied over the cured Aquabead - including CD50
- Is environmentally safe - has low VOC
- Is safe to handle and apply (no need for special clothing, ventilation equipment)
- Can be brushed, dipped or sprayed
- Washes up in water
- Can be reapplied as required

Typical uses: On joinery, doors, interior & exterior woodwork, spa pools & surrounds, sarked ceilings etc. Other products can be applied over Aquabead to obtain the desired finish.

On particle board and kiln dried framing, to give protection from weather, particularly during winter construction – and further protection in case of leaks.

On bricks, plaster, Oamaru stone, Hinuera stone, Mudbricks, Adobe etc to provide water repellency.

On decks and outdoor furniture to give protection, water repellancy and to help stop bleeding of timbers.

On fibrolight to give a natural cleaning finish which will resist dirt build up.

Directions for use: Aquabead is applied neat using a brush, roller, spray or by dipping.

Apply second coat after 48 hours.

Coverage: Coverage varies according to porosity of the substrate.

As a guide – 12-15 sq metres per litre on dressed timber

7-10 sq meters per litre on rough sawn timber

3-5 sq meters per litre on masonry

Safety: Avoid direct contact of product with skin and eyes.

Wash hands and exposed skin before meals and after work.

Do not eat, drink or smoke when using product or handling treated timber.

Wash overalls regularly, remove wet contaminated clothing immediately.

Avoid contamination of any water supply with the chemical or empty container. Keep away from food, drink and animal foodstuffs. Keep out of reach of children. Dispose of empty container safely.

First Aid: Wash splashes off skin immediately. If eyes become contaminated, flush with water for 15 minutes. If swallowed give a glass of two of water then cause vomiting by putting a finger down the throat. Repeat until vomit fluid is clear in appearance. Call a doctor.

Conditions Of Supply: All goods supplied by Churton Pacific Ltd., are physically suitable for use in the matter stated. However as we cannot exercise control over the mixing and use of products, or weather conditions, no responsibility will be accepted for any damage or injury, which may arise from careless storage, handling, application or use.

Information: Specific information relating to the application and handling of this product may be obtained solely from Churton Pacific Limited, 15A Vega Place, Mairangi Bay Industrial Estate, AUCKLAND. Phone/Fax (09) 478-4370, 0800 107 555.