CHURTON PACIFIC LIMITED

NATURAL TIMBER FINISHING & PRESERVATIVES
CEDAR RESTORATION SERVICES

TELEPHONE: 64 9 478 4370 FAX: 64 9 478 4370 EMAIL: CHURTON@CHURTON.COM
ADDRESS: 15A VEGA PLACE, MAIRANGI BAY INDUSTRIAL PARK, AUCKLAND
P.O. BOX 302 276, NORTH HARBOUR, AUCKLAND
WWW.CHURTON.COM

Technical Data Sheet

WETSHIELD

Low Sheen Urethane

Characteristics: A quality water soluble low sheen urethane that has been adapted to give protection to timber that has been oiled with CD50.

Features: Protects against bleach marking on timber caused by mild acid or alkali splash eg in spa rooms, toilets, kitchens, etc.

Protects against dirt and grime, and gives a microscopic film surface that can be cleaned.

Typical uses: On doors, window sills and other interior working surfaces to enable them to be wiped clean.

Protection from splash marks in kitchens, toilets, spa rooms etc

For use where CD50 treated timber abuts plasterboard, plaster, gib or any other absorbent material. Stripe the mating edges or surfaces of the timber with two coats of WETSHIELD to prevent cross diffusion into the porous material.

Can also be used directly on timber not protected with CD50

Directions for use: Surface must be clean, free of dirt, grease and dust.

Previously oiled timber should be dry rag wiped immediately prior to application

Stir frequently before and during use. Do not shake.

First coat

- Do not thin - use neat
- For oiled timbers, rub on with a soft cloth and leave to cure 6 hours minimum before next coat
- For non-oiled timbers, apply by brushing

Second coat

- Subsequent coats (as required) can be applied by brush - allow 4-6 hours between coats

Product will be fully cured 24 hours after last application

Coverage: Approximately 9 to 11 square metres per litre, depending on surface and method of application.

Wash up with warm soapy water.

Safety: Wear suitable clothing/overalls, synthetic rubber/ PVC gloves and eye protection when diluting concentrate and when spraying or handling freshly treated timber. Use a respirator if spraying product.

Use with adequate ventilation

Avoid direct contact of product with skin and eyes.

Avoid contamination of any water supply with the chemical or empty container. Keep out of reach of children. Dispose of empty container safely.

First Aid: If eyes become contaminated, flush with water for 15 minutes. Get medical attention if irritation persists.

Breathing difficulty - leave the area immediately to obtain fresh air. Get medical attention if problem persists.

If swallowed give plenty of water to dilute and get medical advice.

Conditions Of Supply:

All goods supplied by Churton Pacific Ltd., are produced under rigidly controlled procedures which assure the purchaser that at the time of sale the products are physically suitable for use in the matter stated. However as we cannot exercise control over the mixing and use of products, or weather conditions, no responsibility will be accepted for any damage or injury, which may arise from careless storage, handling, application or use.

Information: Specific information relating to the application and handling of this product may be obtained from Churton Pacific Limited, 15A Vega Place, Mairangi Bay Industrial Estate, AUCKLAND. Phone/Fax (09) 478-4370, 0800 107 555